



DuraChimney® II

DuraVent Approved for Air-Cooled Listing

DuraVent DuraChimney II is now listed as the only approved air-cooled chimney on the new High Country™ NZ7000 and NZ8000 low mass fireplaces, offered from Napoleon Fireplaces.

DuraChimney II is a double-wall, air-cooled chimney system for use with masonry fireplaces which burn wood, oil, coal, or gas, and is UL Listed to UL 103 as well as ULC S604 standards.

10" diameter DuraChimney II is approved for use as an air-cooled chimney and the following parts are available:

NOTE: M&G DuraVent DuraChimney II is allowed for use on this product.

Use DuraVent DuraChimney II brand of air-cooled chimney.

CHIMNEY COMPONENTS	DuraChimney II
12" (305mm) Chimney Section	10DCA-12
48" (1219mm) Chimney Section	10DCA-48
36" (914mm) Chimney Section	10DCA-36
15° Elbow	10DCA-E15
Chase Top Flashing	10DCA-CTF
Chimney Cap	10DCA-VC
Firestop / Radiation Shield	10DCA-RRS
CHIMNEY COMPONENTS	Wolf Steel
Air Housing*	NZAC10KT
Anchor Plate	10DCA-AP

* Required for DuraChimney II

NOTE: Follow the chimney manufacturer's instructions for installing the chimney.



To learn more about this approval, please contact
M&G DuraVent Customer Service.
800.835.4429
customerservice@duravent.com