



All-Fuel, Double-Wall Chimney System
Factory-built 2100° F / 650°C Chimney.
Listed to ULC S629 and UL 103HT.

Premium Quality.
Premium Performance.
Premium Value.

DuraVent®

DuraTech® Premium

Premium Quality. Premium Performance. Premium Value.

Introducing **DuraTech® Premium Chimney.**

Factory-built 2100° F / 650°C double-wall chimney design developed and tested to outperform, especially in colder climates. Available in 6", 7", & 8" diameters.

Use with Confidence:

Fully listed to the stringent Canadian ULC S629 standard and approved to UL 103HT for use in the United States.

Thick Two-Inch Insulated Wall:

No need to worry about the continuous radiation shields required on one-inch chimney designs. Twice the insulation means faster start-ups, higher flue-gas temperatures, and improved draft performance. High flue-gas temperatures also minimize the condensation leading to creosote formation.

Factory-Insulated Parts:

With today's drive towards home-heating efficiency, attic insulation levels are getting deeper, and maintaining a continuous air barrier is more important than ever. Our design is up to the challenge. We have a full range of pre-insulated factory parts including ceiling supports, attic radiation shields, wall thimbles, and specialized wall firestops. It all adds up to ensure you get the most from your hard-earned heating dollars.

Universal Support Hardware:

Majority of support components can be used with all three sizes of pipe – 6", 7" and 8". This simplifies inventory and adds to ease-of-installation and versatility.

Twist-Lock Connection:

No need to bother with screws or awkward locking bands. DuraTech® Premium twist-locks together quickly with just a one-eighth turn.

Clearances:

Approved with two-inch clearance to combustible materials.



For more information on our products, visit www.duravent.com

DuraVent®

www.duravent.com | 800-835-4429

LXXX_81000XXX_Sales Sheet_DuraTech Premium_04-10-18_V1

