

Fluoroelastomer Adhesives, Coatings, Sealants, and Caulk

TECHNICAL DATA

Pelseal® 2531

General Information:

- Liquid Fluoroelastomer; Caulk, Sealant, Adhesive
- Solvent-Borne
- One Component

Typical Values:	
VOC (g/l):	400
Color:	Black
Viscosity (cps):	500,000
Weight Solid (%):	70.0
Volume Non-Volatile (%), ASTM D-2697:	50.4
Density (lb./gallon):	11.2
Specific Gravity (Water = 1):	1.34
Tensile Strength (psi), ASTM D-2370 (Post Cure):	1,000
Elongation (%), ASTM D-2370 (Post Cure):	200
Theoretical Coverage (cubic inches /gallon):	116
11 oz. / 325 ml Cartridge - 1/8" x 1/8" bead:	61.9 Linear Feet
Operating Temperature:	-40° F to 400° F, with excursions to
	500° F

Values are not intended for use in preparation of specifications.

Pelseal® is a registered trademark of Pelseal® Technologies, LLC

Disclaimer Information and suggestions supplied by Pelseal® Technologies, LLC ("Pelseal"), whether in published literature or otherwise, including samples, are based on technical data that Pelseal believes to be reliable. Such information and suggestions are supplied without charge and their use, and the use of Pelseal's products, are beyond Pelseal's control. Pelseal's products, information and suggestions are intended for use by persons having technical skill and know-how in the industry. Such persons are responsible, at their sole discretion and risk, to satisfy themselves regarding the suitability of Pelseal's products, information and suggestions for their particular use and circumstances. Any handling precaution information is given with the understanding that those using it will satisfy themselves that their particular use conditions present no health or safety hazards. **Warranty** For a period of one (1) year from the certification date listed on Pelseal's products, Pelseal certifies that the products meet Pelseal's specifications in effect as of such certification date. Pelseal shall not be responsible for any failure arising out of, and this limited warranty shall be rendered null and void by, any one or more of the following: (i) Pelseal is not paid in full for the products purchased by buyer, (ii) buyer or any end-user does not cooperate with Pelseal's reasonable investigation of any alleged non-conforming product, or (iii) damage in transit, abuse, misuse, improper maintenance, acts of nature, accidents (e.g. dropping the products), alteration of the product or causes beyond Pelseal's reasonable control. In the event that any Pelseal, prejat. OTHER THAN THE WARRANTY SET FORTH ABOVE, PELSEAL MAKES NO OTHER WARRANTIES OR REPRESENTATIONS OF ANY KIND, EXPRESS OR IMPLIED, AS TO THE CONDITION, DESCRIPTION, FITNESS FOR A PARTICULAR PURPOSE, MERCHANTABILITY, OR AS TO ANY OTHER MATTER. PELSEAL SHALL NOT BE LIABLE OR RESPONSIBLE FOR ANY CONSEQUENTIAL, INDIRECT, INCIDENTAL, PUNITIVE OR SPECIAL DAMAGES.

3161 State Road, Unit G, Bensalem, PA19020 USA Questions? Visit us at: www.pelseal.com Or call (215)-245-0581 fx (215)-245-7606 email: sales@pelseal.com