


It's the "Swiss Army Knife" of Ceiling Support Boxes!

DuraVent®


You asked for more versatility, and we delivered.

Why stock two or more ceiling supports when a single box can be used for all three vertical chimney applications?


That's what you get with the **DTC Reduced Clearance Ceiling Support** for use with DuraTech Canada insulated chimney.



FLAT CEILING



VAULTED CEILING



CATHEDRAL CEILING



DTC-RCS shown with standard Square-to-Round Collar

This new box design fulfills plenty of other common requests too. The list of standard features below will quickly make this your go-to ceiling support:

- 1. Works within Smaller Openings** – The DTC-RCS is factory-tested and certified to reduce surrounding clearances-to-combustibles around the box from 2" to just 1". This allows a 6" DTC chimney to be installed within a 10 & 1/8" x 10 & 1/8" opening. Versions of the DTC-RCS are also available for use with 7" and 8" pipe too, although framing dimensions will correspond to diameter.
- 2. Can act as an Attic Radiation Shield*** - When the ceiling penetration is right at the attic, fix the square-to-round collar (included at no extra charge) around the chimney, then push down atop the box to complete the assembly. This eliminates the need for a separate Attic Radiation Shield component. Aside from one less part to worry about, assembly is quicker.
- 3. Integrated Starter Collar and Built-In Stovepipe Adapter** – Like other DTC ceiling supports, the first chimney length simply twist-locks within the support, and the adapter works with both single-wall and double-wall stovepipe. No additional parts are required. Providing the vapor barrier is secured to the box perimeter, this factory-sealed assembly will help to minimize leakage of air from conditioned spaces (warm) up into unconditioned spaces (cold).
- 4. Comes with Finish Trim** – Our two-piece adjustable trim is pre-painted to match the box. The overlapping ends allow it to work with both flat and pitched ceilings. The end-result is a clean, professional finish.
- 5. Best of all, the DTC-RCS is insulated!** – We include a batt of rockwool insulation with each & every DTC-RCS box we sell. For both new constructions and retrofit installations. Ideal for today's high-efficient homes.

*DTC-RCS Reduced Clearance Ceiling Support has a standard 24" Box Height. A minimum of 3 1/2" must protrude below the ceiling to ensure appropriate clearances for stovepipe. If additional box height is required, a matching 24" Support Box Extension (DTC-SE) is available. With 2" overlap, provides up to 22" in additional height. Be sure to read instructions closely prior to starting an installation.

Leaders in-Venting Innovation™

www.duravent.com | 800-835-4429



Sales Sheet_DuraTech Canada RCS_07-17-18